0001855 / 13110 Date: 07/07/2023



SYNTH-TECH XT SAE 5W-40

DATA SHEET

Description

SYNTH-TECH XT SAE 5W-40 is a HC synthetic high-performance fuel-efficient engine oil of SAE class 5W-40. Synthetic components and an innovative additive system tailored to them ensure compliance with current practical requirements. The significantly improved engine oil quality of SYNTH-TECH XT SAE 5W-40 results in particular from the further improved wear protection as well as improved engine cleanliness, even with extended oil change intervals. The extremely low low-temperature viscosity combined with a safe high-temperature viscosity ensures a high fuel-saving potential. SYNTH-TECH XT SAE 5W-40 is suitable as a high-performance, low-viscosity engine oil for demanding engines. It is recommended for passenger car gasoline and diesel engines, including turbo versions and for direct injection engines, under all operating conditions.

Specification

ACEA A3/B4

API SN/CF

Application recommendation

 BMW Longlife-01
 Fiat 9.55535-M
 MB 229.3

 Opel GM-LL-B-025
 Porsche A40
 PSA B71 2296

Renault RN 0700 / RN 0710 VW 502 00 / 505 00

Product attributes			
Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m³	858
Viscosity kin. 100°C	DIN 51562-1	mm²/s	14,4
Viscosity index	DIN ISO 2909		172
TBN	DIN ISO 3771	mgKOH/g	10,2
Pourpoint	DIN ISO 3016	°C	-42
Flammable COC	DIN ISO 2592	°C	224

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Q**uality.

PROFI-CAR MADE IN GERMANY