0002158 / 14140 Date: 11/13/2023



ECO-DRIVE LONGLIFE 1 SAE 5W-40

DATA SHEET

Description

ECO-DRIVE LONGLIFE 1 SAE 5W-40 is a passenger car engine oil for vehicles with modern exhaust aftertreatment and extended oil change intervals. Can be used in all suitable gasoline and diesel engines. Especially for diesel engines with DPF systems (low SAPS).

Specification

ACEA C3

API SN/CF

Application recommendation

BMW LL-04 Fiat 9.55535-S2 Ford WSS-M2C917-A

GM dexos 2 MB 226.5 MB 229.51

Porsche A40 Renault RN 0700 / 0710 VW 502 00 / 505 00 / 505 01

Product attributes			
Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m³	850
Viscosity 40°C	DIN 51562-1	mm²/s	80,1
Viscosity 100°C	DIN 51562-1	mm²/s	13,6
Viscosity index	DIN ISO 2909		175
TBN	DIN ISO 3771	mgKOH/g	8,0
Pourpoint	DIN ISO 3016	°C	-42
Flammable COC	DIN ISO 2592	°C	232

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

PROFI-CAR MADE IN GERMANY