

TIDAL POWER SUPER UHPD 10W-40

Fully Synthetic Heavy Duty Diesel Engine Oil

TIDAL POWER SUPER UHPD 10W-40 is a high-performance engine oil based on 100% synthetic technology to be used in diesel engines in light- and heavy commercial vehicles with or without turbocharger designed for use in Euro-II, Euro-III, Euro-IV and Euro V emission requirements and engines equipped with EGR and/or SCR exhaust after treatment system. **TIDAL POWER SUPER UHPD 10W-40** is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER SUPER UHPD 10W-40 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Excellent protection against forming of "Bore Polishing".
- Suitable for low emission engine equipped with EGR and SCR technology
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Extended oil drain interval possible

TIDAL POWER SUPER UHPD 10W-40 meets the following performance criteria:

ACEA E4/E7
MTU type 3
Mack EO-N

API CF
Deutz DQC III-10
Scania LDF-3

MB 228.5
Volvo VDS-3
DAF extended drain

MAN M3277
Renault RVI RLD-2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	863
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	85.3
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	13.3
Viscosity Index		ASTM D2270	159
Viscosity CCS @ -25 °C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-38
Total Base Number	mgKOH/g	ASTM D2896	16.2
Sulphated Ash	%Wt	ASTM D874	1.85
Date Issued: 17-6-2021		Supersedes: 13-03-2018	Revision Nr.: 02

