PRODUCT DATA SHEET

HYDRAULIC FLUID



PENTOSIN CHF 11S

Long-Life Synthetic Hydraulic Fluid For Modern Vehicles

DESCRIPTION

Pentosin CHF 11S is a synthetic high performance hydraulic fluid for life-time application in modern vehicle aggregates. Pentosin CHF 11S is especially designed for hydraulics in the automotive industry with the highest technical requirements such as in: power steering, level control, shock absorber, hydro-pneumatic suspension, stability and traction control, hydraulics for convertible tops, central lock systems, etc. It is suitable for all extreme conditions and guarantees full performance from -40°C to over 130°C system temperature.

| SIZE | PART NUMBER | GTIN-13 |
|----------|-------------|---------------|
| 1 Liter | 1405116 | 4008849503016 |
| 5 Liter | 1405216 | 4008849512346 |
| 20 Liter | 1405208 | 4008849522345 |

PRODUCT ATTRIBUTES

| Appearance | Dark Green |
|------------------------------|-----------------------|
| Density at 20°C | 825 kg/m ³ |
| Kinematic Viscosity at 100°C | 6.0 mm²/s |
| Kinematic Viscosity at 40°C | 18.7 mm²/s |
| Kinematic Viscosity at -40°C | 1100 mm²/s |
| Viscosity Index | 313 |
| Pour Point | -57°C/-70.6°F |
| Flash Point | 160°C/320°F |
| Ignition Temperature | 235°C/455°F |

SAFET

YON ALL ROADS

| OE REFERENCE NUMBERS/RECOMMENDATIONS | | |
|---|------------------|--|
| Make | Reference Number | |
| Audi/Volkswagen | G 002 000 A2 | |
| Bentley | RH 5000 | |
| BMW/Mini | 82 11 1 468 041 | |
| BMW/Mini | 82 11 0 148 132 | |
| BMW/Mini | 83 29 0 429 576 | |
| Fendt | X 902 011 622 | |
| Mercedes-Benz | 001 989 24 03 10 | |
| Mercedes-Benz | 001 989 24 03 12 | |
| Mercedes-Benz | Q 1 32 0001 | |
| Porsche | 000 043 203 33 | |
| Saab | 3032 380 | |
| Volvo | 11 61 529 | |

| APPROVALS/SPECIFICATIONS | | |
|--------------------------|-------------------|--|
| Organization Name | Specification Met | |
| Audi/VW | TL 52 146.00 | |
| Bentley | Bentley approved | |
| BMW | BMW approved | |
| Chrysler | Chrysler approved | |
| Dodge | Dodge approved | |
| Fendt | Fendt approved | |
| Ford | Ford WSS-M2C204-A | |
| GM/Opel | GM/Opel approved | |
| Јеер | Jeep approved | |
| MAN | M 3289 | |
| MB | 345.0 | |
| Porsche | Porsche approved | |
| Saab | Saab approved | |
| Volvo | Volvo approved | |
| ZF | ZF TE-ML 02K | |
| DIN | 51 524 T3 | |
| ISO | 7308 | |

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.

© 2011 CRP Industries Inc. Pentosin is a trade name of Deutsche-Pentosin Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions or manufacturing changes.



PENTOCHF11S-071310

CONTITECH REIN AUTOMOTIVE PENTOSIN OE quality brands for import applications.