

the lifeblood of your car



1 L | 1114105-001 4 L | 1114105-004 5 L | 1114105-005 20 L | 1114105-020 20 L | 1114105-B20 60 L | 1114105-D60 60 L | 1114105-D60 208 L | 1114105-D28 208 L | 1114105-D28

RAVENOL BREAK-IN OIL SAE 30

CategoryOther engine oil Item number1114105 Viscosity 30 Specification SAE 30 Oil type Mineral

RAVENOL Break-In Oil SAE 30 is mineral break-in oil for start-up filling and the breaking-in of repaired or overhauled engines.

RAVENOL Break-In Oil SAE 30 dispenses with the use of friction coefficient improving additives (friction modifier) to considerably shorten the break-in phase for rebuilt and modified engines. The piston rings are rapidly seated.

Due to its high content of 2.5% ZDDP (zinc dithiophosphate) (equivalent to approx. 2,500 ppm zinc), **RAVENOL Break-In Oil SAE 30** is especially recommended for driving classic V8 engines with flat tappets.

Application Note

RAVENOL Break-In Oil SAE 30 serves as a classic break-in oil and therefore can only remain in the engine for a short time (max. 1000km). The particularly high levels of anti-wear additives offer extra protection during the critical break-in phase of rebuilt engines. Please pay attention to the specifications of your engine reconditioners during the break-in phase. High engine loads and speeds are to be avoided.

Characteristics

- Very high levels of ZDDP
- No friction modifier
- Breaks the engine in as quickly as possible

Technical Product Data

Density at 20 °C	881,0	kg/m³	EN ISO 12185
Colour	rot		VISUELL
Viscosity at 100 °C	11,0	mm²/s	DIN 51562-1
Viscosity at 40 °C	90,6	mm²/s	DIN 51562-1
Viscosity Index VI	106		DIN ISO 2909
Pourpoint	-27	°C	DIN ISO 3016

Flashpoint	248	°C	DIN EN ISO 2592
Sulphated Ash	0,9	%wt.	DIN 51575

30.12.2021