

SNOWPOWER SYNTH 2T

**2 Stroke engine lubricant for Snowmobile
100% Synthetic - Ester**

TYPE OF USE

100% Synthetic – Ester high performance lubricant specially formulated for snowmobile with 2 Stroke engines working under the most extreme weather conditions: polar cold.

All snowmobile 2 Stroke engines, indirect or direct fuel injection, with oil injector systems or lubricated by premix.
All type of use including racing.

PERFORMANCES

STANDARDS API TC
 ISO -L-EGD
 JASO FD under N° 033MOT075

Lubricant 100% Synthetic - Ester based with low pour point (-48°C / -54°F) formulated with a low content of solvent for easy start up at very low temperature and extreme climate.

Low ash formulation lubricant, Ester based with an effective detergent & dispersant power for a perfect piston, chamber and power valves cleanliness.

The Ester technology limits deposits and maintains engine cleanliness for improved combustion and maximum performance at high engine revs.

Mixes instantaneously with gasoline and remains stable.

Reduces friction and wear to increase engine life.

Anti-smoke.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.



SNOWPOWER SYNTH 2T

**2 Stroke engine lubricant for Snowmobile
100% Synthetic - Ester**

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.873
Viscosity at 40°C (104°F)	ASTM D445	69.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.9 mm ² /s
Viscosity Index	ASTM D2270	149.0
Pour point	ASTM D97	-48.0 °C / -54.0 °F
TBN	ASTM D2896	2.3 mg KOH/g
Flash point	ASTM D92	155.0 °C / 311.0 °F