



ACTRON SAE 5W-40

DATA SHEET

Description

ACTRON SAE 5W-40 is a special HC-synthesis LONGLIFE truck engine oil with fuel economy properties and extended oil change intervals. Can be used in all suitable gasoline, diesel or LPG engines. Turbo and catalyst tested.

Specification

ACEA E4/E7

API CI-4/UHPD

Application recommendation

DAF HP-1/HP-2

DTFR 15B120 (MB 228.5)

MAN M3277

MTU TYP 3

Renault RXD/RLD-2

Scania LDF

Volvo VDS-3

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	858
Viscosity 40°C	DIN 51562-1	mm ² /s	82,8
Viscosity -30°C	DIN 51377	mPa*s	6400
Viscosity 100°C	DIN 51562-1	mm ² /s	13,6
Viscosity index	DIN ISO 2909		167
TBN	DIN ISO 3771	mgKOH/g	12,5
Pourpoint	DIN ISO 3016	°C	-39
Flammable COC	DIN ISO 2592	°C	220

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**